

## The Perfect Balance of Speed, Size, and Memory



**3,985fps @ 1920x1080 | 8GPx/s throughput | 10,000fps @ 1064x768**

### FEATURES + OPTIONS

- HD resolution 1920 x1080 pixel sensor, more pixels = greater accuracy
- Full resolution to 3,980 frames/second, maintaining higher res at higher speeds
- 8 TB internal SSD capacity
- Up to 144 GB of on-board memory for long recordings or multiple buffers
- Internal or external SSD drive for fast data transfer
- Impressive 8.3 GP/sec throughput
- Global electronic shutter to 250 ns\*
- Compatible with all Nikon F and Canon EF mount lenses
- Record up to 500,000 fps
- App-based tablet control via Controller Display Unit (CDU) for simple operation
- Fully compatible with the i-SPEED Software Suite 2.0 for more advanced functions
- Upgrade path between models

\* subject to export regulations

**High performance high-speed camera in a compact and durable form-factor.**



The sealed electronics design of the i-SPEED 5 utilizes an innovative internal cooling system—drawing heat from the inside of the camera and venting it to the atmosphere

**Sublime ease-of-use coupled with full feature functionality**



## IMAGER

<b>Sensor type</b>	Custom CMOS
<b>Sensor resolution</b>	1920 x 1080 pixel
<b>Sensor size</b>	25.920 mm x 14.580 mm
<b>Sensor diagonal</b>	29.74 mm
<b>Pixel size</b>	13.5 µm
<b>Bit depth</b>	12 bit (36 bit color)
<b>ISO (12232-2:2006, D, sat)</b>	Mono ISO 8,500D (sat) / 68,000D (sat) Color ISO 3,060D (sat) / 24,480D (sat)
<b>Maximum frame rate</b>	500,000 fps
<b>Shutter type</b>	Global exposure
<b>Shutter time, standard</b>	1 µs min (standard)
<b>Shutter time, fast mode</b>	250 ns min (export restricted)

## SYNCHRONIZATION and CAPTURE

<b>Trigger</b>	TTL T0 to 0-100%
<b>Trigger modes</b>	Circular, ROC, BROCC
<b>Sync</b>	10 Hz – 350 kHz
<b>Luminance histogram</b>	Iris setting aid tool
<b>i-CHEQ 360</b>	Camera status LEDs
<b>i-FOCUS</b>	Focusing aid tool
<b>i-EXPOSE</b>	High/low exposure highlight
<b>Control</b>	PC or CDUe
<b>IRIG input</b>	IRIG – B to 1 µs
<b>Internal memory</b>	18 GB standard, upgrade to 144 GB

## PHYSICAL and ENVIRONMENTAL

<b>Dimensions inches</b>	5.0 (W) x 5.1 (H) x 12.0 (L)
<b>Dimensions mm</b>	127 (W) x 129 (H) x 305 (L)
<b>Weight</b>	9.9 lb (4.5 kg)
<b>Input voltage</b>	14-36 V
<b>Power consumption</b>	110 W nominal, 150 W max
<b>Mounting</b>	1/4 x 20 and 3/8 x 16 tripod plate
<b>Lens mount</b>	Custom, swappable lens plate
<b>EMC</b>	EN55032-A, EN55024
<b>Safety</b>	BS EN61010-1 (camera), IEC60950 (PSU)
<b>CE marking</b>	EMC directive (camera), EMC directive, LV directive (PSU)
<b>Lead free</b>	RoHS directive
<b>WEEE</b>	Compliant
<b>Temperature °F</b>	14° to 122° operation, -4° to 140° storage
<b>Temperature °C</b>	-10° to +50° operation, -20° to 60° storage
<b>Pressure</b>	71 kpa to 106 kpa
<b>Relative humidity</b>	95% at 104°F non-condensing
<b>Power input connector</b>	4 pin Lemo
<b>Trigger input</b>	BNC 75 Ω
<b>I/O connector</b>	10 pin Lemo, trigger in / sync / exposure out / remote power

## CONNECTIVITY

<b>Video outputs</b>	HD-SDI, HDMI
<b>USB</b>	USB 3
<b>Network</b>	1Gb/s RJ45 / 10 pin Lemo
<b>Video</b>	IXV, AVI (compressed or uncompressed)
<b>Image sequence</b>	TIFF, JPG, RAW
<b>Ethernet control</b>	1 Gb/s
<b>Remote control</b>	Via supplied software

## PC SOFTWARE

<b>Standard control</b>	Control ONE
<b>Premium control</b>	Control MULTI-DAQ
<b>Editing</b>	i-SPEED Movie Maker
<b>Analysis</b>	ProAnalyst® Lite by Xcitex
<b>Viewer</b>	i-SPEED Viewer
<b>Utilities</b>	i-SPEED Lens Calculator, i-SPEED Viewer
<b>Software Developers Kit</b>	C++, LabView
<b>Synchronized data acquisition</b>	USB DAQ, 8 options

## PURCHASING OPTIONS

<b>CDUe</b>	Controller Display Unit
<b>Sensor</b>	Color / Mono
<b>Memory</b>	18 GB (std) / 36 GB / 72 GB / 96 GB / 144GB
<b>Shutter time</b>	1 µs (std) / 250 ns (subject to export restrictions)
<b>Internal SSD</b>	500 GB / 1 TB / 2 TB / 4 TB / 8 TB
<b>External SSD</b>	500 GB / 1 TB / 2 TB
<b>Lens mounts</b>	F mount (Nikkor D) / F mount (Nikkor G) C mount / EF mount
<b>Warranty</b>	1 yr (std) / 2 yr / 3 yr
<b>IRIG</b>	IRIG-B

## FRAME RATES, RESOLUTION, and DURATION

FPS	Resolution	18GB	36GB	72GB	96GB	144GB
100	1920x1080	30.4 sec	60.9 sec	122 sec	162 sec	243 sec
200	1920x1080	15.2 sec	30.4 sec	60.9 sec	81.1 sec	122 sec
300	1920x1080	10.1 sec	20.2 sec	40.5 sec	54 sec	81 sec
500	1920x1080	6.1 sec	12.2 sec	24.3 sec	32.5 sec	49 sec
1,000	1920x1080	3 sec	6.1 sec	12.2 sec	16.2 sec	24 sec
2,000	1920x1080	1.5 sec	3.1 sec	6.1 sec	8.1 sec	12 sec
3,000	1920x1080	1 sec	2 sec	4.1 sec	5.4 sec	8.1 sec
3,985	1920x1080	0.8 sec	1.5 sec	3.1 sec	4.1 sec	6.1 sec
4,980	1512x1081	0.8 sec	1.6 sec	3.2 sec	4.2 sec	6.3 sec
5,000	1512x1080	0.8 sec	1.6 sec	3.2 sec	4.2 sec	6.3 sec
6,382	1344x966	0.8 sec	1.6 sec	3.1 sec	4.2 sec	6.2 sec
7,500	1232x888	0.8 sec	1.6 sec	3.1 sec	4.2 sec	6.3 sec
10,000	1064x768	0.8 sec	1.6 sec	3.2 sec	4.2 sec	6.3 sec
15,000	840x630	0.8 sec	1.6 sec	3.2 sec	4.3 sec	6.5 sec
20,000	728x540	0.8 sec	1.6 sec	3.3 sec	4.4 sec	6.6 sec
50,000	448x324	0.9 sec	1.8 sec	3.6sec	4.7 sec	7.1 sec
100,000	336x198	1 sec	1.9 sec	3.9 sec	5.2 sec	7.7 sec
200,000	336x84	1.1 sec	2.3 sec	4.6 sec	6.1 sec	9.1 sec
300,000	336x48	1.3 sec	2.7 sec	5.3 sec	7.1 sec	10.6 sec
500,000	392x18	1.8 sec	3.7 sec	7.3 sec	9.7 sec	14.6 sec

**Note: Other resolutions and speeds are available.**



info@ix-cameras.com • ix-cameras.com

Specifications subject to change  
Document: DS-508-10.3.18 Copyright © 2018 iX Cameras Ltd.

### United Kingdom

iX Cameras  
Bradley House  
Locks Hill  
Rochford  
Essex, S54 1BB  
T: +44 (0) 1702 540 669

### United States

iX Cameras  
8 Cabot Rd.  
Suite 1800  
Woburn,  
MA, 01801  
T: 339 645 0778

### China

iX Cameras  
Room 1402, Unit 65,  
No 399 Hangting Road,  
Oriental Hong Jing Garden,  
ZhuQiao Town, Shanghai,  
T: +86 186 215 60553

### India

iX Cameras  
J2-101  
Swiss County Thergaon  
Pune,  
411033  
T: 0955 256 5021